



SUSPENSION LADDERS Mod. SCS

Specifically designed for suspension works. The ladder is made of light aluminium alloy, fitted with anti-slippery rungs, with a special track for the anti-fall device and with a galvanised steel supporting hook

Model	Traction breaking load [kN]	Suggested working load [kN]	Length [m]	Section length [m]	Linear mass [kg/m]	Anti-fall device (model) (not included)
SCS 100	15	3	3.5	3.5	3.8	SDA 001
SCS 200	15	3	4.5	4.5	3.8	SDA 001
SCS 300	15	3	6	6	3.8	SDA 001
SCS 301	15	3	6	4+2	3.8	SDA 001

Special models with different lengths can be designed according to customer's needs

OPTIONAL DEVICES

- SDG 004 Swivel hook
- SDT 005 Horizontal beam



ANCHORING LADDERS Mod. SCA

Specifically designed for anchoring works. The ladders are made of light aluminium alloy, with anti-slippery rungs and with galvanised steel suspension hooks. The ladders are supplied with a supplementary swivel hook to be located on the conductor, which allows the ladder to be used in horizontal position. The ladders are available with triangular or trapezoidal section

Model	Bending breaking load [kN]	Suggested working load [kN]	Length [m]	Section length [m]	Linear mass [kg/m]	Section
SCA 700	7.5	1.5	4	4	4	Triangular
SCA 800	7.5	1.5	6	6	4	Triangular
SCA 801	7.5	1.5	6	4+2	4	Triangular
SCA 400	15	3	3.5	3.5	4.7	Trapezoidal
SCA 401	15	3	4.5	4.5	4.7	Trapezoidal
SCA 500	15	3	6.5	4.5+2	4.7	Trapezoidal

Special models with different lengths can be designed according to customer's needs

Certified Quality System
ISO 9001:2000



ANTI-FALL DEVICES SDA

They are individual protective devices to prevent the operator from falling down; they are self-guided and self-locking devices running on a special rigid track and made of light aluminium alloy. They are provided with a polyamide mini energy-absorber and safety spring catch to connect it to the safety harness; the use of the safety harness is compulsory.

They allow the proper movement of the operator along the ladder and, at the same time, they protect him from falling down. End stroke devices are provided in order to avoid that the anti-fall device run away from the anchoring track. These devices comply with the 89/686/CEE European Standard related to the individual protective devices

Model	Breaking load [kN]	Suggested working load [kN]	Nylon rope length [mm]	Mass [kg]
SDA 001	20	1.5	300	0.8
SDA 002	20	1.5	300	0.8
SDA 003	20	1.5	300	0.8